

(12) International Application Status Report

Received at International Bureau: 20 April 2001 (20.04.2001)

Information valid as of: (..)

Report generated on: 21 January 2021 (21.01.2021)

(10) Publication number:

WO2001/076893

(43) Publication date:

18 October 2001 (18.10.2001)

(26) Publication language:

English (EN)

(21) Application Number:

PCT/BR2001/000038

(22) Filing Date:

04 April 2001 (04.04.2001)

(25) Filing language:

English (EN)

(31) Priority number(s):

PI 0001130-4 (BR)

(31) Priority date(s):

05 April 2000 (05.04.2000)

(31) Priority status:

Priority document received (in compliance with PCT Rule 17.1)

(51) International Patent Classification:

B60C 11/02 (2006.01)

(71) Applicant(s):

DREBOR INDÚSTRIA DE ARTEFATOS DE BORRACHA LTDA. [BR/BR]; Avenida V, 502 Distrito Industrial CEP-78098-480 Cuiabá, MT (BR) *(for all designated states except US)*

DRESCH, Eldon [BR/BR]; Rua Atílio Borio, 51 Apt. 2204 CEP-80050-250 Curitiba, PR (BR) *(for US only)*

(72) Inventor(s):

DRESCH, Eldon; Rua Atílio Borio, 51 Apt. 2204 CEP-80050-250 Curitiba, PR (BR)

(74) Agent(s):

ARNAUD, Antonio, M., P.; Rua José Bonifácio, 93 7th floor CEP-01003-901 São Paulo, SP (BR)

(54) Title (EN): A TREAD FOR RETREADING TIRES

(54) Title (FR): SEMELLE POUR RECHAPAGE DE PNEUMATIQUES

(57) Abstract:

(EN): A tread for retreading tires, having an external face (21) provided with the usual grooves (23) and an internal face (22) to be seated and adhered, usually by vulcanization, to the convex external face (11) of a tire carcass (10), from which the compound of the original tread has been totally abraded, said tread (20) presenting a thickness that varies throughout the width thereof, having its internal face (22) defined in a concave arc, with the radius of curvature corresponding to that of the external face (11) of the tire carcass (10) and with its external face (21) being flat or slightly convex, with the radius of curvature substantially larger than that of its internal face (22).

(FR): Cette semelle pour rechapage de pneumatiques comporte une face extérieure (21) dans laquelle sont ménagés les creux habituels (23) ainsi qu'une face intérieure (22) à faire adhérer, d'ordinaire par vulcanisation, à la face extérieure convexe (11) de la carcasse du pneumatique (10), la matière ayant composé le pneumatique d'origine ayant été entièrement abrasée. L'épaisseur de cette semelle (20) varie sur toute sa largeur et sa face intérieure (22) forme un arc concave dont le rayon correspond à celui de la face extérieure (11) de la carcasse, la face extérieure (21) étant plate ou légèrement convexe et ayant un rayon de courbure sensiblement plus important que celui de la face intérieure (22).

International search report:

Received at International Bureau: 08 August 2001 (08.08.2001) [EP]

International Report on Patentability (IPRP) Chapter II of the PCT:

Chapter II demand received: 31 October 2001 (31.10.2001)

(81) Designated States:

AE, AG, AL, AU, BA, BB, BG, BZ, CA, CN, CO, CR, CU, CZ, DM, DZ, EE, GE, HR, HU, ID, IL, IN, IS, JP, KP, KR, LC, LK, LR, LT, LV, MA, MG, MK, MN, MX, NO, NZ, PL, RO, SG, SI, SK, TT, UA, US, UZ, VN, YU, ZA
European Patent Office (EPO) : AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR
African Intellectual Property Organization (OAPI) : BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG
African Regional Intellectual Property Organization (ARIPO) : GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW
Eurasian Patent Organization (EAPO) : AM, AZ, BY, KG, KZ, MD, RU, TJ, TM