

# (12) International Application Status Report

**Received at International Bureau:** 11 May 2006 (11.05.2006)

**Information valid as of:** (..)

**Report generated on:** 16 January 2021 (16.01.2021)

**(10) Publication number:**

WO2006/102371

**(43) Publication date:**

28 September 2006 (28.09.2006)

**(26) Publication language:**

English (EN)

**(21) Application Number:**

PCT/US2006/010325

**(22) Filing Date:**

22 March 2006 (22.03.2006)

**(25) Filing language:**

English (EN)

**(31) Priority number(s):**

60/663,969 (US)

**(31) Priority date(s):**

22 March 2005 (22.03.2005)

**(31) Priority status:**

Priority document received (in compliance with PCT Rule 17.1)

**(51) International Patent Classification:**

G03B 17/08 (2006.01)

**(71) Applicant(s):**

PINOTAGE, L.L.C. [US/US]; 20 East Center Street Fayetteville, AR 72701 (US) *(for all designated states except US)*  
THOMPSON, Robert, Lee [US/US]; 19308 Pinecrest Trail Rogers, AR 72756 (US) *(for US only)*

**(72) Inventor(s):**

THOMPSON, Robert, Lee; 19308 Pinecrest Trail Rogers, AR 72756 (US)

**(74) Agent(s):**

PRATT, Shannon; Wolf, Greenfield & Sacks, P.C 600 Atlantic Avenue Boston, MA 02210 (US)

**(54) Title (EN):** IMAGING DEVICE ASSEMBLY

**(54) Title (FR):** ENSEMBLE DISPOSITIF D'IMAGERIE

**(57) Abstract:**

**(EN):** An assembly for mounting an imaging device, such as a camera, is provided. The assembly may include a housing and an imaging device mounted to the housing. The housing is constructed and arranged in a manner that absorbs and/or dampens a shock and/or vibration to minimize any resulting damage to the imaging device. The assembly may be constructed and arranged to meet MIL-S-901D (NAVY). In one embodiment, resilient and/or robust materials are incorporated into the mounting assembly.

**(FR):** L'invention concerne un ensemble pour le montage d'un dispositif d'imagerie, tel qu'une caméra. L'ensemble peut comprendre un boîtier et un dispositif d'imagerie monté sur le boîtier. Le boîtier est construit et conçu de manière à absorber et/ou à amortir un choc et/ou une vibration afin de réduire au minimum n'importe quel dommage résultant sur le dispositif d'imagerie. L'ensemble peut être construit et conçu pour satisfaire la norme MIL-S-901D (marine de guerre). Dans un mode de réalisation, des matériaux résilients et/ou robustes sont intégrés dans l'ensemble de montage.

**International search report:**

Received at International Bureau: 10 November 2006 (10.11.2006) [EP]

**International Report on Patentability (IPRP) Chapter II of the PCT:**

Not available

**(81) Designated States:**

AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW

European Patent Office (EPO) : AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR

African Intellectual Property Organization (OAPI) : BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG

African Regional Intellectual Property Organization (ARIPO) : BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW

Eurasian Patent Organization (EAPO) : AM, AZ, BY, KG, KZ, MD, RU, TJ, TM