

(12) International Application Status Report

Received at International Bureau: 11 July 2007 (11.07.2007)

Information valid as of: (..)

Report generated on: 16 January 2021 (16.01.2021)

(10) Publication number:

WO2007/148982

(43) Publication date:

27 December 2007 (27.12.2007)

(26) Publication language:

English (EN)

(21) Application Number:

PCT/NO2007/000216

(22) Filing Date:

19 June 2007 (19.06.2007)

(25) Filing language:

English (EN)

(31) Priority number(s):

20062869 (NO)

(31) Priority date(s):

19 June 2006 (19.06.2006)

(31) Priority status:

Priority document received (in compliance with PCT Rule 17.1)

(51) International Patent Classification:

F17C 13/08 (2006.01); F17C 3/02 (2006.01)

(71) Applicant(s):

TANKER ENGINEERING AS [NO/NO]; Pb 1486 Vika N-0116 Oslo (NO) (for all designated states except US)
AARSETH, Harald [NO/NO]; Colbjørnsensgt. 13 N-0256 Oslo (NO) (for US only)

(72) Inventor(s):

AARSETH, Harald; Colbjørnsensgt. 13 N-0256 Oslo (NO)

(74) Agent(s):

OSLO PATENTKONTOR AS; Postboks 7007M N-0306 Oslo (NO)

(54) Title (EN): AN ARRANGEMENT FOR A CYLINDRICAL TANK FOR TRANSPORTATION OF LIQUEFIED GASES AT LOW TEMPERATURE IN A SHIP

(54) Title (FR): SYSTÈME DE RÉSERVOIR CYLINDRIQUE DESTINÉ AU TRANSPORT DE GAZ LIQUÉFIÉ À BASSE TEMPÉRATURE À BORD D'UN NAVIRE

(57) Abstract:

(EN): A horizontal generally cylindrical tank (2) for transportation of liquefied gases at low temperature in a ship is supported in two saddle supports (12) in the ship (1). At each support, the tank has internal reinforcements comprising two adjacent perforated bulkheads (3) and a framework of crossing girders/stiffeners (4-7) welded between the bulkheads (3), thus providing a tank (2) with sufficient strength for a capacity in the range of at least 40.000 - 60.000 m³. A method for securing accurate roundness of the tank in the support area is also described.

(FR): La présente invention concerne un réservoir cylindrique (2) généralement horizontal destiné au transport de gaz liquéfié à basse température à bord d'un navire, qui est soutenu par deux supports de sellettes (12) dans le navire (1). Sur chaque support, le réservoir possède des renforts internes comprenant deux cloisons perforées (3) adjacentes et un cadre composé de traverses/raidisseurs (4-7) soudés entre les cloisons (3), ce qui donne au réservoir (2) une résistance suffisante pour une capacité comprise entre au moins 40 000 et 60 000 m³. L'invention a aussi pour objet un procédé permettant de garantir avec précision la rondeur du réservoir dans la zone de support.

International search report:

Received at International Bureau: 17 September 2007 (17.09.2007) [SE]

International Report on Patentability (IPRP) Chapter II of the PCT:

Not available

(81) Designated States:

AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW
European Patent Office (EPO) : AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL, PT, RO, SE, SI, SK, TR
African Intellectual Property Organization (OAPI) : BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG
African Regional Intellectual Property Organization (ARIPO) : BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW
Eurasian Patent Organization (EAPO) : AM, AZ, BY, KG, KZ, MD, RU, TJ, TM

Declarations:

Declaration made as applicant's entitlement, as at the international filing date, to apply for and be granted a patent (Rules 4.17(ii) and 51bis.1(a)(ii)), in a case where the declaration under Rule 4.17(iv) is not appropriate