

(12) International Application Status Report

Received at International Bureau: 31 July 2008 (31.07.2008)

Information valid as of: 16 January 2009 (16.01.2009)

Report generated on: 25 July 2021 (25.07.2021)

(10) Publication number:

WO2009/013549

(43) Publication date:

29 January 2009 (29.01.2009)

(26) Publication language:

English (EN)

(21) Application Number:

PCT/GB2008/050621

(22) Filing Date:

24 July 2008 (24.07.2008)

(25) Filing language:

English (EN)

(31) Priority number(s):

0714332.4 (GB)

(31) Priority date(s):

24 July 2007 (24.07.2007)

(31) Priority status:

Priority document received (in compliance with PCT Rule 17.1)

(51) International Patent Classification:

G08B 13/16 (2006.01); G08B 29/18 (2006.01)

(71) Applicant(s):

INFRASONIC PULSE SENSING LIMITED [GB/GB]; Solent House 107A Alma Road Portswood Southampton Hampshire SO14 6UY (GB) *(for all designated states except US)*

RUDDOCK, Derek James [GB/GB]; Heathcliff Hill Top Road Hainworth Keighley Yorkshire BD21 5QN (GB) *(for US only)*

(72) Inventor(s):

RUDDOCK, Derek James; Heathcliff Hill Top Road Hainworth Keighley Yorkshire BD21 5QN (GB)

(74) Agent(s):

SANDERSON, James; 34 East Stockwell Street Colchester Essex CO1 1ST (GB)

(54) Title (EN): INFRASONIC INTRUDER ALARM

(54) Title (FR): ALARME ANTI-INTRUSION INFRASONIQUE

(57) Abstract:

(EN): An infrasonic intruder alarm system (100) adapted to detect changes in infrasonic frequency in a defined space (101).

The alarm system (100) comprises a transducer (13) for sensing infrasonic frequency variations, which is adapted to produce an analogue signal (20), a signal amplifier, an analogue to digital converter which is adapted to convert a portion of the analogue signal (20) which crosses at least one predetermined threshold into a digital signature (30), and a processor (15) adapted to compare the digital signature (30) against known digital signatures. An alarm event is triggered if the digital signal (30) produced matches a known signature, and an alarm (17) is activated by the alarm event.

(FR): L'invention concerne un système d'alarme anti-intrusion infrasonique (100) conçu pour détecter des changements dans une fréquence infrasonique dans un espace défini (101). Le système d'alarme (100) comprend un transducteur (13) pour détecter des variations de fréquence infrasonique, qui est conçu pour produire un signal analogique (20), un amplificateur de signal, un convertisseur analogique-numérique qui est conçu pour convertir une partie du signal analogique (20) qui franchit au moins un seuil prédéterminé en une signature numérique (30), et un processeur (15) conçu pour comparer la signature numérique (30) à des signatures numériques connues. Un événement d'alarme est déclenché si le signal numérique (30) produit correspond à une signature connue, et une alarme (17) est activée par l'événement d'alarme.

International search report:

Received at International Bureau: 09 December 2008 (09.12.2008) [EP]

International Report on Patentability (IPRP) Chapter II of the PCT:

Not available

(81) Designated States:

AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW

European Patent Office (EPO) : AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR

African Intellectual Property Organization (OAPI) : BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG

African Regional Intellectual Property Organization (ARIPO) : BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW

Eurasian Patent Organization (EAPO) : AM, AZ, BY, KG, KZ, MD, RU, TJ, TM