

(12) International Application Status Report

Received at International Bureau: 13 July 2009 (13.07.2009)

Information valid as of: 03 February 2010 (03.02.2010)

Report generated on: 21 January 2021 (21.01.2021)

(10) Publication number:

WO2010/020451

(43) Publication date:

25 February 2010 (25.02.2010)

(26) Publication language:

German (DE)

(21) Application Number:

PCT/EP2009/057840

(22) Filing Date:

23 June 2009 (23.06.2009)

(25) Filing language:

German (DE)

(31) Priority number(s):

10 2008 041 359.3 (DE)

(31) Priority date(s):

20 August 2008 (20.08.2008)

(31) Priority status:

Priority document received (in compliance with PCT Rule 17.1)

(51) International Patent Classification:

H01R 13/08 (2006.01); **H01R 13/631** (2006.01)

(71) Applicant(s):

ROBERT BOSCH GMBH [DE/DE]; Postfach 30 02 20 70442 Stuttgart (DE) (*for all designated states except US*)
KUPERBERG, Ilya [DE/DE]; Am Wald 40 76149 Karlsruhe (DE) (*for US only*)

(72) Inventor(s):

KUPERBERG, Ilya; Am Wald 40 76149 Karlsruhe (DE)

(74) Common Representative(s):

ROBERT BOSCH GMBH; Postfach 30 02 20 70442 Stuttgart (DE)

(54) Title (EN): ELECTRICAL CONNECTING ELEMENT HAVING AN INHERENTLY RIGID CONTACT PIN

(54) Title (FR): ÉLÉMENT DE CONNEXION ÉLECTRIQUE AVEC UNE POINTE DE CONTACT INTRINSÈQUEMENT RIGIDE

(54) Title (DE): ELEKTRISCHES VERBINDUNGSELEMENT MIT EINEM EIGENSTEIFEN KONTAKTSTIFT

(57) Abstract:

(EN): The invention relates to an electrical connecting element comprising an inherently rigid contact pin which comprises a connection area at one end. The contact pin (6) is connected at the other end to an inherently elastic connection element (4).

(FR): L'invention concerne un élément de connexion électrique avec une pointe de contact intrinsèquement rigide qui comporte en une extrémité une zone de raccordement. Il est prévu que la pointe de contact (6) soit reliée à l'autre extrémité avec un élément de raccordement (4) intrinsèquement élastique.

(DE): Die Erfindung betrifft ein elektrisches Verbindungselement mit einem eigensteifen Kontaktstift, der einendig einen Anschlussbereich aufweist. Es ist vorgesehen, dass der Kontaktstift (6) anderendig mit einem eigenelastischen Anschlusselement (4) verbunden ist.

International search report:

Received at International Bureau: 21 September 2009 (21.09.2009) [EP]

International Report on Patentability (IPRP) Chapter II of the PCT:

Not available

(81) Designated States:

AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC,

LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW
European Patent Office (EPO) : AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR
African Intellectual Property Organization (OAPI) : BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG
African Regional Intellectual Property Organization (ARIPO) : BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW
Eurasian Patent Organization (EAPO) : AM, AZ, BY, KG, KZ, MD, RU, TJ, TM