

(12) International Application Status Report

Received at International Bureau: 12 December 2016 (12.12.2016)

Information valid as of: 14 December 2016 (14.12.2016)

Report generated on: 29 February 2020 (29.02.2020)

(10) Publication number:

WO2017/095784

(43) Publication date:

08 June 2017 (08.06.2017)

(26) Publication language:

English (EN)

(21) Application Number:

PCT/US2016/063936

(22) Filing Date:

29 November 2016 (29.11.2016)

(25) Filing language:

English (EN)

(31) Priority number(s):

62/260,802 (US)

(31) Priority date(s):

30 November 2015 (30.11.2015)

(31) Priority status:

Priority document received (in compliance with PCT Rule 17.1)

(51) International Patent Classification:

C03C 23/00 (2006.01); **C03C 17/36** (2006.01); **C03C 27/06** (2006.01); **E06B 3/66** (2006.01); **E06B 3/663** (2006.01); **B29C 65/16** (2006.01); **C03C 27/10** (2006.01)

(71) Applicant(s):

CORNING INCORPORATED [US/US]; 1 Riverfront Plaza Corning, New York 14831 (US) *(for all designated states)*

(72) Inventor(s):

STRELTSOV, Alexander Mikhailovich; 10879 Hidden Meadow Trail Corning, New York 14830 (US)

THOMAS, John Christopher; 77 Hedy Creek Road Elmira, New York 14905 (US)

(74) Agent(s):

WEGMANN, Zachary J.; Corning Incorporated Intellectual Property Department SP-Ti-03-01 Corning, New York 14831 (US)

(54) Title (EN): LASER WELDING TRANSPARENT GLASS PANES USING A LOW EMISSIVITY COATING

(54) Title (FR): SOUDAGE AU LASER DE VITRES TRANSPARENTES À L'AIDE D'UN REVÊTEMENT À FAIBLE ÉMISSIVITÉ

(57) Abstract:

(EN): A sealed article and methods of making the same. The sealed article includes a first and second glass pane. The first and second glass panes include inner surfaces opposite outer surfaces and at least one outer edge. The second glass pane is spaced apart from and positioned substantially parallel to the first glass pane with a low emissivity layer there between. An seal is formed between the first and second glass panes contiguous the low emissivity layer.

(FR): L'invention concerne un objet fermé hermétiquement et des procédés de fabrication associés. L'objet fermé hermétiquement comprend une première et une deuxième vitre. La première et la deuxième vitre comprennent des surfaces internes à l'opposé des surfaces externes et au moins un bord extérieur. La deuxième vitre est écartée de la première vitre et positionnée de manière sensiblement parallèle à celle-ci, une couche à faible émissivité étant située entre elles. Un joint est formé entre la première et la deuxième vitre, contigu à la couche à faible émissivité.

International search report:

Received at International Bureau: 20 February 2017 (20.02.2017) [EP]

International Report on Patentability (IPRP) Chapter II of the PCT:

Not available

(81) Designated States:

AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG,

PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW

European Patent Office (EPO) : AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR

African Intellectual Property Organization (OAPI) : BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG

African Regional Intellectual Property Organization (ARIPO) : BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW

Eurasian Patent Organization (EAPO) : AM, AZ, BY, KG, KZ, RU, TJ, TM