

(12) International Application Status Report

Received at International Bureau: 25 October 2017 (25.10.2017)

Information valid as of: 28 March 2018 (28.03.2018)

Report generated on: 24 July 2019 (24.07.2019)

(10) Publication number:

WO2018/074292

(43) Publication date:

26 April 2018 (26.04.2018)

(26) Publication language:

Japanese (JA)

(21) Application Number:

PCT/JP2017/036746

(22) Filing Date:

11 October 2017 (11.10.2017)

(25) Filing language:

Japanese (JA)

(31) Priority number(s):

2016-204179 (JP)

(31) Priority date(s):

18 October 2016 (18.10.2016)

(31) Priority status:

Priority document received (in compliance with PCT Rule 17.1)

(51) International Patent Classification:

G06F 1/26 (2006.01); **G06F 1/32** (2006.01); **G09G 3/20** (2006.01); **G09G 5/00** (2006.01); **H04N 5/225** (2006.01); **H04N 5/64** (2006.01)

(71) Applicant(s):

KONICA MINOLTA, INC. [JP/JP]; 2-7-2, Marunouchi, Chiyoda-ku, Tokyo 1007015 (JP) *(for all designated states)*

(72) Inventor(s):

ISHIKAWA, Tetsuya; c/o KONICA MINOLTA, INC., 2-7-2, Marunouchi, Chiyoda-ku, Tokyo 1007015 (JP)

(74) Agent(s):

KOYO INTERNATIONAL PATENT FIRM; 17F., Tokyo Takarazuka Bldg., 1-1-3, Yurakucho, Chiyoda-ku, Tokyo 1000006 (JP)

(54) Title (EN): WEARABLE DEVICE

(54) Title (FR): DISPOSITIF VESTIMENTAIRE

(54) Title (JA): ウエアラブル機器

(57) Abstract:

(EN): In this wearable device, in order to suppress power consumption and increase operation efficiency while suppressing component failures, it is possible to selectively set a normal activation mode or a non-normal activation mode for a control unit. When the normal activation mode is set, the control unit is activated by turning on a power source switch and is stopped by turning off the power source switch, and when the non-normal activation mode is set, the control unit is activated by satisfying a predetermined condition even if the power source switch is not turned on.

(FR): Dans le présent dispositif vestimentaire, afin de limiter la consommation d'énergie et d'accroître le rendement de fonctionnement tout en limitant les défaillances de composants, il est possible de spécifier sélectivement un mode d'activation normal ou un mode d'activation non normal pour une unité de commande. Lorsque le mode d'activation normal est spécifié, l'unité de commande est activée en allumant un interrupteur de source d'alimentation et est arrêtée en éteignant l'interrupteur de source d'alimentation, et lorsque le mode d'activation non normal est spécifié, l'unité de commande est activée en satisfaisant une condition prédéterminée même si l'interrupteur de source d'alimentation n'est pas allumé.

(JA): 部品の破損を抑制しつつも、電力消費を抑え、作業効率を高めるために、ウェアラブル機器は、制御部が、通常起動モードと非通常起動モードとを選択的に設定可能となっており、通常起動モードの設定時には、制御部が電源スイッチのオン操作により起動され、オフ操作により停止し、非通常起動モードの設定時には、制御部が電源スイッチのオン操作がなされなくても所定条件を満たすことで起動するようになっている。

International search report:

Received at International Bureau: 25 December 2017 (25.12.2017) [JP]

International Report on Patentability (IPRP) Chapter II of the PCT:

Not available

(81) Designated States:

AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW

European Patent Office (EPO) : AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR

African Intellectual Property Organization (OAPI) : BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG

African Regional Intellectual Property Organization (ARIPO) : BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW

Eurasian Patent Organization (EAPO) : AM, AZ, BY, KG, KZ, RU, TJ, TM