

(12) International Application Status Report

Received at International Bureau: 18 December 2017 (18.12.2017)

Information valid as of: 19 April 2018 (19.04.2018)

Report generated on: 24 September 2019 (24.09.2019)

(10) Publication number:

WO2018/106768

(43) Publication date:

14 June 2018 (14.06.2018)

(26) Publication language:

English (EN)

(21) Application Number:

PCT/US2017/064845

(22) Filing Date:

06 December 2017 (06.12.2017)

(25) Filing language:

English (EN)

(31) Priority number(s):

62/431,227 (US)

(31) Priority date(s):

07 December 2016 (07.12.2016)

(31) Priority status:

Priority document received (in compliance with PCT Rule 17.1)

(51) International Patent Classification:

G01N 3/14 (2006.01); *G01N 3/34* (2006.01)

(71) Applicant(s):

MTS SYSTEMS CORPORATION [US/US]; 14000 Technology Drive Eden Prairie, MN 55344-2290 (US) *(for all designated states)*

(72) Inventor(s):

LUCACHICK, Glenn; 8605 Poplar Bridge Curve Bloomington, MN 55437 (US)

MEYER, Richard, A.; 1197 Wildwood Court Chaska, MN 55318 (US)

JOSEPHSON, Robert; 49 N Madison Ave #402 Sturgeon Bay, WI 54235 (US)

(74) Agent(s):

KOEHLER, Steven M.; Westman, Champlin & Koehler, P.A. 900 Second Avenue South, Suite 1400 Minneapolis, MN 55402-3319 (US)

(54) Title (EN): IMPACT SENSOR BODY HAVING FLEXURE MEMBER

(54) Title (FR): CORPS DE CAPTEUR D'IMPACT COMPORTANT UN ÉLÉMENT DE FLEXION

(57) Abstract:

(EN): An impact sensor body (100) for sensing Charpy impact force is disclosed. The sensor body (100) includes a body of material with a plurality of apertures (120,130). The apertures (120,130) are configured within the body of material to form a flexure member (125) orthogonal to a direction of motion to strike an object.

(FR): L'invention concerne un corps de capteur d'impact (100) permettant de détecter une force d'impact par essai Charpy. Le corps de capteur (100) comprend un corps de matériau ayant une pluralité d'ouvertures (120, 130). Les ouvertures (120, 130) sont configurées à l'intérieur du corps de matériau pour former un élément de flexion (125) orthogonal à une direction de mouvement pour frapper un objet.

International search report:

Received at International Bureau: 16 April 2018 (16.04.2018) [EP]

International Report on Patentability (IPRP) Chapter II of the PCT:

Not available

(81) Designated States:

AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA,

PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW

European Patent Office (EPO) : AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR

African Intellectual Property Organization (OAPI) : BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG

African Regional Intellectual Property Organization (ARIPO) : BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW

Eurasian Patent Organization (EAPO) : AM, AZ, BY, KG, KZ, RU, TJ, TM