

(12) International Application Status Report

Received at International Bureau: 10 January 2018 (10.01.2018)

Information valid as of: 27 September 2018 (27.09.2018)

Report generated on: 23 October 2019 (23.10.2019)

(10) Publication number:

WO2018/189961

(43) Publication date:

18 October 2018 (18.10.2018)

(26) Publication language:

Japanese (JA)

(21) Application Number:

PCT/JP2017/045563

(22) Filing Date:

19 December 2017 (19.12.2017)

(25) Filing language:

Japanese (JA)

(31) Priority number(s):

2017-080426 (JP)

(31) Priority date(s):

14 April 2017 (14.04.2017)

(31) Priority status:

Priority document received (in compliance with PCT Rule 17.1)

(51) International Patent Classification:

H04N 5/232 (2006.01); **G06T 3/40** (2006.01)

(71) Applicant(s):

SHARP KABUSHIKI KAISHA [JP/JP]; 1, Takumi-cho, Sakai-ku, Sakai City, Osaka 5908522 (JP) *(for all designated states)*

(72) Inventor(s):

KITAURA, Ryuhji
TOKUI, Kei

(74) Agent(s):

HARAKENZO WORLD PATENT & TRADEMARK; Daiwa Minamimorimachi Building, 2-6, Tenjinbashi 2-chome Kita, Kita-ku, Osaka-shi, Osaka 5300041 (JP)

(54) Title (EN): IMAGE PROCESSING DEVICE, TERMINAL DEVICE, AND IMAGE PROCESSING PROGRAM

(54) Title (FR): DISPOSITIF DE TRAITEMENT D'IMAGE, DISPOSITIF TERMINAL ET PROGRAMME DE TRAITEMENT D'IMAGE

(54) Title (JA): 画像処理装置、端末装置、および画像処理プログラム

(57) Abstract:

(EN): The purpose of the present invention is to suppress the output of useless images. An image processing device (1) is provided with a composition correction unit (2) that, on the basis of an input image, outputs an output image the composition of which is in accordance with the input image. According to the input image, the composition correction unit (2) determines whether to output the output image. When the composition correction unit (2) outputs the output image, at least one of the size change, translation amount and rotation amount in correction of the input image into the output image is equal to or greater than a threshold value.

(FR): Le but de la présente invention est de supprimer la sortie d'images inutiles. Un dispositif de traitement d'image (1) est pourvu d'une unité de correction de composition (2) qui, sur la base d'une image d'entrée, délivre une image de sortie dont la composition est conforme à l'image d'entrée. En fonction de l'image d'entrée, l'unité de correction de composition (2) détermine s'il faut délivrer l'image de sortie. Lorsque l'unité de correction de composition (2) délivre l'image de sortie, au moins une valeur parmi celles d'un changement de taille, d'une quantité de translation et d'une quantité de rotation, dans la correction de l'image d'entrée vers l'image de sortie, est supérieure ou égale à une valeur seuil.

(JA): 有用ではない画像の出力を抑制する。画像処理装置(1)は、入力画像に基づき、当該入力画像に応じた構図の出力画像を出力する構図補正部(2)を備え、前記構図補正部(2)は、前記入力画像に応じて、前記出力画像を出力するか否かを決定し、前記構図補正部(2)が前記出力画像を出力するとき、前記入力画像から当該出力画像への補正におけるサイズの変化、並進量および回転量の少なくとも1つが閾値以上である。

International search report:

Received at International Bureau: 05 March 2018 (05.03.2018) [JP]

International Report on Patentability (IPRP) Chapter II of the PCT:

Not available

(81) Designated States:

AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW

European Patent Office (EPO) : AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR

African Intellectual Property Organization (OAPI) : BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG

African Regional Intellectual Property Organization (ARIPO) : BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW

Eurasian Patent Organization (EAPO) : AM, AZ, BY, KG, KZ, RU, TJ, TM