

(12) International Application Status Report

Received at International Bureau: 28 February 2018 (28.02.2018)

Information valid as of: 19 November 2018 (19.11.2018)

Report generated on: 22 April 2019 (22.04.2019)

(10) Publication number:

WO2018/225301

(43) Publication date:

13 December 2018 (13.12.2018)

(26) Publication language:

Japanese (JA)

(21) Application Number:

PCT/JP2018/005519

(22) Filing Date:

16 February 2018 (16.02.2018)

(25) Filing language:

Japanese (JA)

(31) Priority number(s):

2017-113073 (JP)

(31) Priority date(s):

08 June 2017 (08.06.2017)

(31) Priority status:

Priority document received (in compliance with PCT Rule 17.1)

(51) International Patent Classification:

H02M 3/155 (2006.01); *H02M 1/12* (2006.01); *H02M 7/48* (2007.01)

(71) Applicant(s):

mitsubishi electric corporation [JP/JP]; 7-3, Marunouchi 2-chome, Chiyoda-ku, Tokyo 1008310 (JP) *(for all designated states)*

(72) Inventor(s):

SUGAWARA, Retsu; c/o MITSUBISHI ELECTRIC CORPORATION, 7-3, Marunouchi 2-chome, Chiyoda-ku, Tokyo 1008310 (JP)

AWANE, Kazutoshi; c/o MITSUBISHI ELECTRIC CORPORATION, 7-3, Marunouchi 2-chome, Chiyoda-ku, Tokyo 1008310 (JP)

(74) Agent(s):

FUKAMI PATENT OFFICE, P.C.; Nakanoshima Festival Tower West, 2-4, Nakanoshima 3-chome, Kita-ku, Osaka-shi, Osaka 5300005 (JP)

(54) Title (EN): POWER CONVERSION DEVICE

(54) Title (FR): DISPOSITIF DE CONVERSION D'ÉNERGIE

(54) Title (JA): 電力変換装置

(57) Abstract:

(EN): A capacitor (C) has a parasitic inductance component (Lp), and is electrically connected between a positive electrode line (PL1) and a negative electrode line (NL). A converter (10) includes a reactor (Lc) that is provided on the positive electrode line (PL1), and is configured so as to convert a direct current voltage smoothed by a capacitor (C1). An inverter (20) is configured so as to perform DC-AC conversion between the converter (10) and an alternating current motor (M) by means of a switching control. The inductance of a path (PATH1) connecting the direct current power supply (B) and the capacitor (C) to each other, said path being a part of the positive electrode line (PL1), is smaller than the inductance of a path (PATH2) connecting the direct current power supply (B) and the capacitor (C) to each other, said path being a part of the negative electrode line (NL). The difference between the inductance of the path (PATH2) and the inductance of the path (PATH1) is smaller than double the parasitic inductance component (Lp).

(FR): Un condensateur (C) a une composante d'inductance parasite (Lp), et est électriquement connecté entre une ligne d'électrode positive (PL1) et une ligne d'électrode négative (NL). Un convertisseur (10) comprend une bobine de réactance (Lc) qui est disposée sur la ligne d'électrode positive (PL1), et est configuré de façon à convertir une tension continue lissée par un condensateur (C1). Un onduleur (20) est configuré de façon à effectuer une conversion CC-CA entre le convertisseur (10) et un moteur à courant alternatif (M) au moyen d'une commande de commutation. L'inductance d'un trajet (PATH1) connectant l'un à l'autre l'alimentation en courant continu (B) et le condensateur (C), ledit trajet faisant partie de la ligne d'électrode positive (PL1), est inférieure à l'inductance d'un trajet (PATH2) connectant l'un à l'autre l'alimentation en courant continu (B) et le condensateur (C), ledit trajet faisant partie de la ligne d'électrode négative (NL). La différence entre l'inductance du trajet (PATH2) et l'inductance du trajet (PATH1) est inférieure au double de la composante d'inductance parasite (Lp).

(JA): コンデンサ(C)は、寄生インダクタンス成分(L_p)を有し、正極線(P L 1)と負極線(N L)との間に電氣的に接続される。コンバータ(1 0)は、正極線(P L 1)に設けられたリアクトル(L_c)を含み、コンデンサ(C 1)により平滑化された直流電圧の電圧変換を行なうように構成される。インバータ(2 0)は、コンバータ(1 0)と交流モータ(M)との間での直流交流変換をスイッチング制御により行なうように構成される。正極線(P L 1)のうち直流電源(B)とコンデンサ(C)とを結ぶ経路(P A T H 1)のインダクタンスは、負極線(N L)のうち直流電源(B)とコンデンサ(C)とを結ぶ経路(P A T H 2)のインダクタンスよりも小さい。経路(P A T H 2)のインダクタンスと経路(P A T H 1)のインダクタンスとの差は、寄生インダクタンス成分(L_p)の2倍未満である。

International search report:

Received at International Bureau: 30 April 2018 (30.04.2018) [JP]

International Report on Patentability (IPRP) Chapter II of the PCT:

Not available

(81) Designated States:

AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW

European Patent Office (EPO) : AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR

African Intellectual Property Organization (OAPI) : BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG

African Regional Intellectual Property Organization (ARIPO) : BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW

Eurasian Patent Organization (EAPO) : AM, AZ, BY, KG, KZ, RU, TJ, TM