

# (12) International Application Status Report

**Received at International Bureau:** 06 September 2017 (06.09.2017)

**Information valid as of:** 12 February 2019 (12.02.2019)

**Report generated on:** 21 August 2019 (21.08.2019)

**(10) Publication number:**

WO2019/043761

**(43) Publication date:**

07 March 2019 (07.03.2019)

**(26) Publication language:**

Japanese (JA)

**(21) Application Number:**

PCT/JP2017/030790

**(22) Filing Date:**

28 August 2017 (28.08.2017)

**(25) Filing language:**

Japanese (JA)

**(51) International Patent Classification:**

**G09F 9/00** (2006.01); **G02F 1/13** (2006.01); **G02F 1/1333** (2006.01); **G02F 1/1335** (2006.01); **G09F 9/30** (2006.01); **G09F 9/35** (2006.01)

**(71) Applicant(s):**

SHARP KABUSHIKI KAISHA [JP/JP]; 1, Takumi-cho, Sakai-ku, Sakai City, Osaka 5908522 (JP) *(for all designated states)*

**(72) Inventor(s):**

KANEKO, Seiji

KANZAKI, Yohsuke

SAITOH, Takao

MIWA, Masahiko

YAMANAKA, Masaki

**(74) Agent(s):**

HARAKENZO WORLD PATENT & TRADEMARK; Daiwa Minamimorimachi Building, 2-6, Tenjinbashi 2-chome Kita, Kita-ku, Osaka-shi, Osaka 5300041 (JP)

**(54) Title (EN):** INFLEXIBLE SUBSTRATE PROVIDED WITH DISPLAY ELEMENT, AND FLEXIBLE DISPLAY DEVICE MANUFACTURING METHOD

**(54) Title (FR):** SUBSTRAT RIGIDE POURVU D'UN ÉLÉMENT D'AFFICHAGE, ET PROCÉDÉ DE FABRICATION DE DISPOSITIF D'AFFICHAGE SOUPLE

**(54) Title (JA):** 表示素子を備えた非可撓性基板及び可撓性表示装置の製造方法

**(57) Abstract:**

**(EN):** In a right-side PI layer inclined area (RPA), a photosensitive PI layer (10), which covers a ground PI layer (2) exposed from an inorganic film composed of a moisture-proof layer (3), a gate insulation layer (5), a second insulation layer (7), and a third insulation layer (9), is formed.

**(FR):** Selon la présente invention, dans une zone inclinée de couche PI côté droit (RPA), une couche PI photosensible (10), qui recouvre une couche PI de mise à la terre (2) visible au niveau d'un film inorganique composé d'une couche étanche à l'humidité (3), d'une couche d'isolation de grille (5), d'une deuxième couche d'isolation (7) et d'une troisième couche d'isolation (9), est formée.

**(JA):** 右側PI層傾斜領域(RPA)においては、防湿層(3)とゲート絶縁層(5)と第2絶縁層(7)と第3絶縁層(9)との無機膜から露出する下地PI層(2)を覆う感光性PI層(10)が形成されている。

**International search report:**

Received at International Bureau: 04 December 2017 (04.12.2017) [JP]

**International Report on Patentability (IPRP) Chapter II of the PCT:**

Not available

**(81) Designated States:**

AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW

European Patent Office (EPO) : AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR

African Intellectual Property Organization (OAPI) : BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG

African Regional Intellectual Property Organization (ARIPO) : BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW

Eurasian Patent Organization (EAPO) : AM, AZ, BY, KG, KZ, RU, TJ, TM