

# (12) International Application Status Report

**Received at International Bureau:** 22 August 2018 (22.08.2018)

**Information valid as of:** 06 February 2019 (06.02.2019)

**Report generated on:** 19 September 2019 (19.09.2019)

**(10) Publication number:**

WO2019/044480

**(43) Publication date:**

07 March 2019 (07.03.2019)

**(26) Publication language:**

Japanese (JA)

**(21) Application Number:**

PCT/JP2018/030227

**(22) Filing Date:**

13 August 2018 (13.08.2018)

**(25) Filing language:**

Japanese (JA)

**(31) Priority number(s):**

2017-166608 (JP)

**(31) Priority date(s):**

31 August 2017 (31.08.2017)

**(31) Priority status:**

Priority document received (in compliance with PCT Rule 17.1)

**(51) International Patent Classification:**

*C01B 33/18* (2006.01); *G02F 1/1339* (2006.01)

**(71) Applicant(s):**

UBE EXSYMO CO., LTD. [JP/JP]; 9-19, Nihonbashi-Tomizawacho, Chuo-ku, Tokyo 1030006 (JP) *(for all designated states)*

**(72) Inventor(s):**

MIYOSHI, Hidenori; c/o UBE EXSYMO CO., LTD., 9-19, Nihonbashi-Tomizawacho, Chuo-ku, Tokyo 1030006 (JP)  
GOTOU, Kenta; c/o UBE EXSYMO CO., LTD., 9-19, Nihonbashi-Tomizawacho, Chuo-ku, Tokyo 1030006 (JP)

**(74) Agent(s):**

ONDA, Makoto; 12-1, Ohmiya-cho 2-chome, Gifu-shi, Gifu 5008731 (JP)

**(54) Title (EN):** BLACK POWDER, AND METHOD FOR PRODUCING SAME

**(54) Title (FR):** POUDRE NOIRE ET SA MÉTHODE DE PRODUCTION

**(54) Title (JA):** 黒色粉体及びその製造方法

**(57) Abstract:**

**(EN):** The present invention addresses the problem of providing: a black powder which enables the achievement of higher voltage-resistant performance; and a method for producing the black powder. The black powder according to the present disclosure is composed of carbon-containing silica particles. Each of the silica particles has a single-layer structure. The content of carbon in the surface of each of the silica particles is 1% by mass or less. The content of carbon in the surface of each of the silica particles can be measured by an X-ray photoelectron spectroscopy method.

**(FR):** La présente invention aborde le problème de fournir : une poudre noire qui permet d'obtenir des performances de résistance à la tension plus élevées ; et une méthode de production de la poudre noire. La poudre noire selon la présente invention est composée de particules de silice contenant du carbone. Chacune des particules de silice a une structure monocouche. La teneur en carbone dans la surface de chacune des particules de silice est de 1 % en masse ou moins. La teneur en carbone dans la surface de chacune des particules de silice peut être mesurée par une méthode de spectroscopie photoélectronique des rayons X.

**(JA):** より高い耐電圧性能を得ることができる黒色粉体及びその製造方法を提供することを課題とする。本開示の黒色粉体は、炭素を含有するシリカ粒子から構成される。シリカ粒子は、単層構造を有する。シリカ粒子の表面に含まれる炭素の含有量は、1質量%以下である。シリカ粒子の表面に含まれる炭素の含有量は、X線光電子分光法により測定される。

**International search report:**

Received at International Bureau: 22 October 2018 (22.10.2018) [JP]

**International Report on Patentability (IPRP) Chapter II of the PCT:**

Not available

**(81) Designated States:**

AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW

European Patent Office (EPO) : AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR

African Intellectual Property Organization (OAPI) : BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG

African Regional Intellectual Property Organization (ARIPO) : BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW

Eurasian Patent Organization (EAPO) : AM, AZ, BY, KG, KZ, RU, TJ, TM