









(V)



















实施例号	1	2	3	4	5	6	7	8
P	高达 100 %	高达 100 %	高达 100 %	高达 100 %	高达 100 %	高达 100 %	高达 100 %	高达 100 %
C [重量%]	0	2.9	3.0	3.2	3.3	3.1	3.0	2.7
E1 [ppm]	1,203	1,201	1,189	1,252	1,100	1,010	1,128	1,035
E2 [ppm]	1,857	2,101	2,068	2,043	2,038	1,922	1,919	1,908
E3 [ppm]	1,922	2,048	1,995	1,999	2,089	1,972	1,950	1,951
E4 [ppm]	2,392	1,869	1,363	2,030	1,756	1,955	1,846	1,644

实施例号	1	2	3	4	5	6	7	8
		低 MVR,	低 MVR,	高 MVR,	高 MVR,			
Mw [g/mol]	170,000	185,500	185,900	177,200	167,800	156,400	155,200	158,700
MVR [g/10 min]	13.4	8.4	7.1	11.1	11.3	17.3	16.8	17.7
维卡软化点 [°C]	47.7	38.9	38.7	39.4	38.2	39.4	39.2	39.9
体积密度 [g/l]	588	608	595	599	617	618	619	618
屈服应力 [MPa]	4.0	D型	D型	D型	D型	D型	D型	D型
E模数 [MPa]	81.25	84.2	97.4	83.6	46.8	49.5	50.6	36.1
肖氏A压缩	-	78	78	80	77	82	81	70
肖氏D压缩	-	24	25	26	25	27	26	25
YI	11.2	13.4	14.4	13.0	12.5	15.0	17.0	15.1
透明度 [%]	81.8	79.9	81.9	81.7	81.2	81.8	82.1	81.4
雾度 [%]	15.4	27.2	21.3	17.8	22.7	13.6	13.1	24.4
明晰度[%]	96.4	68.8	70.3	71.1	63.0	88.0	90.8	74.8