


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : F03D 3/04	A1	(11) International Publication Number: WO 95/08062 (43) International Publication Date: 23 March 1995 (23.03.95)
<p>(21) International Application Number: PCT/GR94/00022</p> <p>(22) International Filing Date: 13 September 1994 (13.09.94)</p> <p>(30) Priority Data: 930100377 16 September 1993 (16.09.93) GR</p> <p>(71) Applicant (for all designated States except US): KOFINA, Elvira [GR/GR]; 20 Diamantidou Street, GR-154 52 Palaio Psychico (GR).</p> <p>(71)(72) Applicant and Inventor: KOFINAS, Zacharias [GR/GR]; 13 Kissavou Street, GR-154 52 Palaio Psychico (GR).</p>	<p>(81) Designated States: AM, AU, BB, BG, BR, BY, CA, CN, CZ, FI, GE, HU, JP, KG, KP, KR, KZ, LK, LT, LV, MD, MG, MN, NO, NZ, PL, RO, RU, SI, SK, TJ, TT, UA, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD).</p> <p>Published With international search report. With amended claims.</p> <p>Date of publication of the amended claims: 6 April 1995 (06.04.95)</p>	

(54) Title: SHIELDED WINDMILL



(57) Abstract

The present invention refers to a method and a mechanism for engaging great amounts of aeolian energy and transform it into electric energy by means of a big horizontal, rotating iron shaft 6-20 m long and with a diameter of 16-50 cm. The said shaft is supplied with four rows of frames covered with canvas or nylon sheets. Moreover, the horizontal shaft is furnished with a second rotary motion changing its direction. Two kinds of protective windscreens whose surfaces are covered with nylon or aluminium sheets stapled together form also part of the invention.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgystan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo			SE	Sweden
CH	Switzerland	KR	Republic of Korea	SI	Slovenia
CI	Côte d'Ivoire	KZ	Kazakhstan	SK	Slovakia
CM	Cameroon	LI	Liechtenstein	SN	Senegal
CN	China	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TG	Togo
CZ	Czech Republic	LV	Latvia	TJ	Tajikistan
DE	Germany	MC	Monaco	TT	Trinidad and Tobago
DK	Denmark	MD	Republic of Moldova	UA	Ukraine
ES	Spain	MG	Madagascar	US	United States of America
FI	Finland	ML	Mali	UZ	Uzbekistan
FR	France	MN	Mongolia	VN	Viet Nam
GA	Gabon				

AMENDED CLAIMS

[received by the International Bureau on 10 February 1995 (10.02.95);
original claims 1-11 replaced by amended claims 1-6 (2 pages)]

1. Method for engaging aeolian energy and transformation thereof into electric energy by means of generators characterized in that it consists of a wired turbine with "horizontal shaft around which a rigid cylindrical blade rotor revolves and said rotor comprises rectangular
5 blades equipped either with concave surfaces or planar bent surfaces towards the upwind direction, blades which also have voids between the hub and one half the radius of the blade rotor so that the said blade rotor has the capability of being oriented into the prevailing wind direction.
- 10 2. Method for engaging aeolian energy and transformation thereof into electric energy by means of generators as claimed in Claim 1, characterized in that the wind turbine comprises two vertical converging rigid planar surfaces the minimum horizontal distance of which equals the length of the blade rotor shaft and the height of
15 which is at least twice the diameter of the blade rotor and in such a way so that the entire aeolian device is supported by a circular concrete base used as a platform orientation.
3. Method for engaging aeolian energy and transformation thereof
20 into electric energy by means of generators as claimed in Claim 2, characterized in that the wind turbine consists of two metal pylons which support the two ends of the rotor blade shaft and of a third metal pylon which supports the central section of the rotor blade shaft which is divided in two parts.
- 25 So that said pylons are supported each by four wheels attached to the base of each pylon so that said wheels are able to roll on a pair of concentric circular metal tracks.
4. Method for engaging aeolian energy and transformation thereof into electric energy by means of generators as claimed in Claim 3,
30 characterized in that the wind turbine's concrete circular base is equipped with an inclined planar structure and the said inclined structure has the capacity of rotating around a vertical axis without touching the ground, with the inclined structure's maximum height being greater than that of the blade rotor shaft's and said inclined

35 structure has its upper surface covered by an appropriately smooth material of small air drag friction coefficient.

5. Method for engaging aeolian energy and transformation thereof into electric energy by means of generators as claimed in Claim 4, characterized in that the wind turbine is equipped with a pair of
40 vertical planar structures, structures which have their internal surfaces covered by an appropriately smooth material of small air drag friction coefficient and said pair of structures are divided into two parts, the one nearest to the wind turbine being rigidly connected to the outer converging surface of the inclined structure so that said
45 pair of vertical surfaces and the inclined structure can rotate in unisome around a vertical axis, and the other part of the pair of vertical structures is anchored to the ground in such a way so that an open circuit wind tunnel is formed, the axis of which coincides with the direction of the
50 prevailing winds so that the tunnel's largest cross section is upwind and the tunnel's smallest cross section is downwind adjacent to the rotor blades leading edges.

6. Method for engaging aeolian energy and transformation thereof into electric energy by means of generators as claimed in Claim 5,
55 characterized in that the wind turbine's horizontal shaft, the inclined structure and the pair of vertical structures may be rigidly locked and non rotatable around a vertical axis.