


## PATENT COOPERATION TREATY

## PCT

## INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

(Chapter II of the Patent Cooperation Treaty)

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference 12583-102	<b>FOR FURTHER ACTION</b>		See Form PCT/IPEA/416
International application No. PCT/US08/81765	International filing date ( <i>day/month/year</i> ) 30 October 2008 (30.10.2008)	Priority date ( <i>day/month/year</i> ) 02 November 2007 (02.11.2007)	
International Patent Classification (IPC) or national classification and IPC IPC: <b>A23B 4/03</b> (2006.01) USPC: 99/495			
Applicant DKB HOUSEHOLD USA CORP.			
<p>1. This report is the international preliminary examination report, established by this International Preliminary Examining Authority under Article 35 and transmitted to the applicant according to Article 36.</p> <p>2. This REPORT consists of a total of <u>7</u> sheets, including this cover sheet.</p> <p>3. This report is also accompanied by ANNEXES, comprising:</p> <p>a. <input type="checkbox"/> (<i>sent to the applicant and to the International Bureau</i>) a total of ___ sheets, as follows:</p> <p style="margin-left: 40px;"><input type="checkbox"/> sheets of the description, claims and/or drawings which have been amended and are the basis of this report and/or sheets containing rectifications authorized by this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions).</p> <p style="margin-left: 40px;"><input type="checkbox"/> sheets which supersede earlier sheets, but which this Authority considers contain an amendment that goes beyond the disclosure in the international application as filed, as indicated in item 4 of Box No. I and the Supplemental Box.</p> <p>b. <input type="checkbox"/> (<i>sent to the International Bureau only</i>) a total of (indicate type and number of electronic carrier(s)) _____, containing a sequence listing and/or tables related thereto, in electronic form only, as indicated in the Supplemental Box Relating to Sequence Listing (see Section 802 of the Administrative Instructions).</p>			
<p>4. This report contains indications relating to the following items:</p> <p><input checked="" type="checkbox"/> Box No. I Basis of the report</p> <p><input type="checkbox"/> Box No. II Priority</p> <p><input type="checkbox"/> Box No. III Non-establishment of opinion with regard to novelty, inventive step and industrial applicability</p> <p><input type="checkbox"/> Box No. IV Lack of unity of invention</p> <p><input checked="" type="checkbox"/> Box No. V Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement</p> <p><input type="checkbox"/> Box No. VI Certain documents cited</p> <p><input type="checkbox"/> Box No. VII Certain defects in the international application</p> <p><input type="checkbox"/> Box No. VIII Certain observations on the international application</p>			
Date of submission of the demand 02 June 2009 (02.06.2009)		Date of completion of this report 23 July 2010 (23.07.2010)	
Name and mailing address of the IPEA/ US Mail Stop PCT, Attn: IPEA/US Commissioner for Patents P.O. Box 1450 Alexandria, Virginia 22313-1450		Authorized officer TOM DUNN 	
Facsimile No.		Telephone No. 571-272-1700	

## INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/US08/81765

**Box No. I Basis of the report**1. With regard to the **language**, this report is based on:

- the international application in the language in which it was filed.
- a translation of the international application into English, which is the language of a translation furnished for the purposes of:
- international search (under Rules 12.3(a) and 23.1(b))
- publication of the international application (under Rule 12.4(a))
- international preliminary examination (under Rules 55.2(a) and/or 55.3(a))

2. With regard to the **elements** of the international application, this report is based on (*replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report*):

- the international application as originally filed/furnished
- the description:  
pages 1-9 as originally filed/furnished  
pages\* NONE received by this Authority on \_\_\_\_\_  
pages\* NONE received by this Authority on \_\_\_\_\_
- the claims:  
pages 10-12 as originally filed/furnished  
pages\* NONE as amended (together with any statement) under Article 19  
pages\* NONE received by this Authority on \_\_\_\_\_  
pages\* NONE received by this Authority on \_\_\_\_\_
- the drawings:  
pages 1-7 as originally filed/furnished  
pages\* NONE received by this Authority on \_\_\_\_\_  
pages\* NONE received by this Authority on \_\_\_\_\_
- a sequence listing and/or any related table(s) - see Supplemental Box Relating to Sequence Listing.

3.  The amendments have resulted in the cancellation of:

- the description, pages NONE \_\_\_\_\_
- the claims, Nos. NONE \_\_\_\_\_
- the drawings, sheets/figs NONE \_\_\_\_\_
- the sequence listing (*specify*): \_\_\_\_\_
- any table(s) related to the sequence listing (*specify*): \_\_\_\_\_

4.  This report has been established as if (some of) the amendments annexed to this report and listed below had not been made, since they have been considered to go beyond the disclosure as filed, as indicated in the Supplemental Box (Rule 70.2(c)).

- the description, pages \_\_\_\_\_
- the claims, Nos. \_\_\_\_\_
- the drawings, sheets/figs \_\_\_\_\_
- the sequence listing (*specify*): \_\_\_\_\_
- any table(s) related to the sequence listing (*specify*): \_\_\_\_\_

5.  This report has been established taking into account the **rectification of an obvious mistake** authorized by or notified to this Authority under Rule 91 (Rule 70.2(e)).*\* If item 4 applies, some or all of those sheets may be marked "superseded."*

## INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.  
PCT/US08/81765**Box No. V Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement**

## 1. Statement

Novelty (N)	Claims <u>2, 6-8, 10, 12-14, 16, 18</u>	YES
	Claims <u>1, 3-5, 9, 11, 15, 17</u>	NO
Inventive Step (IS)	Claims <u>NONE</u>	YES
	Claims <u>1-18</u>	NO
Industrial Applicability (IA)	Claims <u>1-18</u>	YES
	Claims <u>NONE</u>	NO

## 2. Citations and Explanations (Rule 70.7)

Please See Continuation Sheet

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.  
PCT/US08/81765**Supplemental Box**

In case the space in any of the preceding boxes is not sufficient.

Continuation of:

**V. 2. Citations and Explanations:**

Claims 1, 3-5, 9, 11, 15 and 17 lack novelty under PCT Article 33(2) as being anticipated by US 5,865,109 A to Bull.

As per claim 1, Bull discloses a drive assembly for a drying device (salad spinner 10), said drive assembly comprising: a driving mechanism (ratchet teeth 48, clutch 52, 60; pinion gear teeth 58, hub 72) mechanically coupled (via fastener 76) to a rotatable lid (turret 26), wherein said lid is configured to mate with a rotatable basket (colander 14) having a plurality of apertures (perforation 16, 18) (FIG. 1-3, col 2, ln 33-37, 50-56, from 63-67 to col 3, ln 1-19); and a handle (drive handle 32) pivotally attached (via fastener 35) to a cover assembly (lid 20) (FIG. 1, 2, col 2, ln 57-62), said handle configured to actuate said driving mechanism upon rotation of said handle about an axis from a first position (left) to a second position (right) (driving mechanism is engaged when handle is rotated in arc from left side to right side) (FIG. 3-7, col 1, ln 45-56).

As per claim 3, Bull discloses the drive assembly of claim 1, and further wherein said driving mechanism comprises a rack (intermediate section 44 with ratchet teeth 48) and a pinion (pinion gear teeth 58 on central tubular section 54) (FIG. 2, 3, from col 2, ln 63-67 to col 3, ln 1-3).

As per claim 4, Bull discloses the drive assembly of claim 3, and further wherein said rack is configured to slideably engage said pinion upon rotation of said handle (driving mechanism is engaged when handle is rotated in arc from left side to right side) (FIG. 3-7, col 1, ln 45-56).

As per claim 5, Bull discloses the drive assembly of claim 3, wherein said driving mechanism further comprises a clutch assembly (clutch housing 52, clutch assembly 60) coupled to said pinion (gear teeth 58) and a sprag assembly (clutch assembly 60) configured such that said sprag assembly engages said clutch assembly when said handle rotates (in an arc) from said first position to said second position (driving mechanism is engaged when handle is rotated in arc from left side to right side) (FIG. 3-7, col 1, ln 45-56, and from col

## INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.  
PCT/US08/81765

## Supplemental Box

2, ln 57-67 to col 3, ln 1-19).

As per claim 9, Bull discloses a drying device (salad spinner 10), comprising: a bowl (12) having a top edge 925) and an opening defined by said top edge (FIG. 2, 3); a basket (colander 14) disposed within said bowl and rotatable about a first axis (center of bowl) with respect to said bowl, said basket comprising an upper edge and a plurality of apertures (perforation 16, 18) (FIG. 2, 3, col 1, ln 45-49, and col 2, ln 33-44); a cover assembly (lid 20) removably configured to mate with said top edge of said bowl, said cover assembly comprising a top side, a bottom side, and a rotatable lid (turret 26) attached to said bottom side and configured to mate with said upper edge of said basket when said cover assembly is positioned upon said top edge of said bowl (FIG. 2, 3, col 2, ln 45-56); and a drive assembly associated with said cover assembly, said drive assembly comprising a driving mechanism (ratchet teeth 48, clutch 52, 60; pinion gear teeth 58, hub 72) mechanically coupled (via fastener 76) to said lid, said driving mechanism comprising a rack (intermediate section 44 with ratchet teeth 48) and a pinion (pinion gear teeth 58 on central tubular section 54) engageable with said rack (FIG. 2, 3, from col 2, ln 63-67 to col 3, ln 1-19), and a handle (drive handle 32) pivotally attached (via fastener 35) to said cover assembly (FIG. 1, 2, 4, col 2, ln 57-62); wherein said handle rotates (in arc) about a second axis (center of post 36) and moves said rack which rotates said pinion about said first axis imparting rotational energy to said lid and said basket (driving mechanism is engaged when handle is rotated in arc from left side to right side) (FIG. 3-7, col 1, ln 45-56).

As per claim 11, Bull discloses the device of claim 9, and further wherein said driving mechanism further comprises a clutch assembly (clutch housing 52, clutch assembly 60) coupled to said pinion (gear teeth 58) and a sprag assembly (clutch assembly 60) configured such that said sprag assembly engages said clutch assembly when said handle rotates (in an arc) from said first position to said second position (driving mechanism is engaged when handle is rotated in arc from left side to right side) (FIG. 3-7, col 1, ln 45-56, and from col 2, ln 57-67 to col 3, ln 1-19).

As per claim 15, Bull discloses a method for drying food (salad), comprising the steps of: providing a drying device (salad spinner 10), said device comprising: a container (bowl 12) having a top edge (25) and an opening defined by said top edge (FIG. 2, 3); a basket (colander 14) disposed within said container, said basket having a plurality of apertures (perforation 16, 18) and an upper edge (FIG. 2, 3, col 2, ln 33-37, 45-49); a cover assembly (lid 20) removably configured to mate with said top edge of said container, said cover assembly comprising a bottom side and a lid (turret 26) attached to said bottom side and configured to mate with said upper edge of said basket when said cover assembly is positioned upon said top edge of said container (FIG. 1-3, col 2, ln 45-56); a drive assembly associated with said cover assembly, said drive assembly comprising a driving mechanism (ratchet teeth 48, clutch 52, 60; pinion gear teeth 58, hub 72)

mechanically coupled (via fastener 76) to said rotatable lid (FIG. 2, 3, from col 2, ln 63-67 to col 3, ln 1-19), and a handle (drive handle 32) pivotally attached (via fastener 35) to said cover assembly (FIG. 1, 2, col 2, ln 57-62); placing food containing moisture within said basket; positioning said cover assembly upon said top edge of said container such that said rotatable lid mates with said top edge of the basket; actuating said handle to engage said driving mechanism to rotate said lid and said basket about an axis in order to remove said moisture from said food; and removing said cover assembly such that said food may be removed from said basket (FIG. 1-7, col 1, ln 9-19, 39-40, and abstract).

As per claim 17, Bull discloses the method of claim 15, and further wherein said driving mechanism further comprises a rack (intermediate section 44 with ratchet teeth 48) and a pinion (pinion gear teeth 58 on central tubular section 54) engageable with said rack (FIG. 3, 4, from col 2, ln 63-67 to col 3, ln 1-3).

Claims 6-8 and 12-14 lack an inventive step under PCT Article 33(3) as being obvious over Bull, in view of US 6,018,883 A to Mulhauser.

As per claim 6, Bull discloses the drive assembly of claim 1, but does not disclose the further claim limitation of Mulhauser, namely, wherein a locking mechanism (latch 132) is positioned on a top side of said cover assembly (24) and is configured to prevent said handle (handle structure 94) from moving from said second position (down at cover) to said first position (up, away from cover) (FIG. 2, 3, 5, 6, 11, 12, 13, and col 5, ln 45-57).

It would have been obvious to one skilled in the art to modify the Bull drying device handle and drive assembly and to add the Mulhauser sliding locking mechanism in order to hold the handle in place in the second position. Such locking mechanism would serve to stop the device operation and ready the unit for storage mode.

As per claim 7, Bull and Mulhauser disclose the drive assembly of claim 6, and Mulhauser further discloses wherein said locking mechanism releasably engages (projection 136 of latch 132 is placed in by sliding the latch) an opening (slot 99) in said handle when said handle is in said second position (down at cover) (FIG. 6, 12, and col 5, ln 45-57).

As per claim 8, Bull and Mulhauser disclose the drive assembly of claim 6, and Mulhauser further discloses wherein said locking mechanism is configured to remain stationary when said handle is in said first position (up, away from cover) (latch 132 is positioned in its initial, non-engaging, location, where it does not interfere with normal handle operation; FIG. 3).

## INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.  
PCT/US08/81765

## Supplemental Box

As per claim 12, Bull discloses the device of claim 9, but does not disclose the further claim limitation of Mulhauser, namely, wherein a locking mechanism (latch 132) is positioned on said top side of said cover assembly (24) configured to prevent said handle (handle structure 94) from moving from said second position (down at cover) to said first position (up, away from cover) (FIG. 2, 3, 5, 6, 11, 12, 13, and col 5, ln 45-57).

It would have been obvious to one skilled in the art to modify the Bull drying device handle and to add the Mulhauser sliding locking mechanism in order to hold the handle in place in the second position. Such locking mechanism would serve to stop the device operation and ready the unit for storage mode.

As per claim 13, Bull and Mulhauser disclose the device of claim 12, and Mulhauser further discloses wherein said locking mechanism releasably engages (projection 136 of latch 132 is placed in by sliding the latch) an opening (slot 99) in said handle when said handle is in said second position (down at cover) (FIG. 6, 12, and col 5, ln 45-57).

As per claim 14, Bull and Mulhauser disclose the device of claim 12, and Mulhauser further discloses wherein said locking mechanism is configured to remain stationary when said handle is in said first position (up, away from cover) (latch 132 is positioned in its initial, non-engaging, location, where it does not interfere with normal handle operation; FIG. 3).

Claims 2, 10, 16 and 18 lack an inventive step under PCT Article 33(3) as being obvious over Bull, in view of US 2007/0137504 A1 to Wan et al. (hereinafter 'Wan'), and further in view of US 4,052,092 A to Bergen.

As per claim 2, Bull discloses the drive assembly of claim 1, but does not disclose further comprising a rod connecting said driving mechanism to said handle, as per the combination of Wan and Bergen as detailed below.

Wan discloses a salad spinner (10') that uses a drive mechanism (300) with a linearly actuating horizontal slider (310') and gear train (320') with leading gear (321') which acts as a straight rack. Rack meshes with second gear (322'), which acts as a pinion, so that gear train 320' serves to rotate the center ratchet assembly (400') to spin basket (200') (FIG. 17, 18B, 21, 23C, and para [0105, 0108, 0112]).

It would have been obvious to one skilled in the art to modify the Bull handle and drive mechanism as per Wan, such that the handle would linearly slide a straight rack which would act to rotate a pinion to spin the basket. The straight rack would be a simpler, more efficient means to rotate the pinion than the Bull curved rack member.

Bergen discloses a latching device where the rack and pinion operation provides a simplified arrangement for translating pivotal thumb lever movement into spindle rotational movement to turn a knob (col 9, ln 50-53). Lever (88) is pivotably mounted to frame (24), and has a narrow, elongated extension, (latch actuating end part (92)), which serves as the rod which is connected to rack plate (42) via the notch in the bottom of actuator plate (50). End part (92) linearly slides rack plate (42) in rack recess (28) of the frame. Rack plate includes rack (46), which meshes with pinion (52). Depressing the lever pivots the end part (rod), which slides the rack, rotating the pinion, and thus turning the knob (FIG. 1, 3, 5, 7, col 5, ln 28-36, 48-62, col 6, ln 41-64, col 7, ln 1-12, and col 8, ln 51-58).

It would have been obvious to one skilled in the art to modify the Bull/Wan handle and drive mechanism as per Bergen to add the end part extension (rod) from the handle lever as a means to slide the drive mechanism rack. Such design enables the user to employ a more effective force translation by the handle/rod pumping action in order to rotate the pinion and basket, while additionally providing a second, lowered handle position for improved storage of the device.

As per claim 10, Bull discloses the device of claim 9, but does not disclose wherein said driving assembly further comprises a rod connecting said handle to said driving mechanism, as per the combination of Wan and Bergen.

Wan discloses a salad spinner (10') that uses a drive mechanism (300) with a linearly actuating horizontal slider (310') and gear train (320') with leading gear (321') which acts as a straight rack. Rack meshes with second gear (322'), which acts as a pinion, so that gear train 320' serves to rotate the center ratchet assembly (400') to spin basket (200') (FIG. 17, 18B, 21, 23C, and para [0105, 0108, 0112]).

It would have been obvious to one skilled in the art to modify the Bull handle and drive mechanism as per Wan, such that the handle would linearly slide a straight rack which would act to rotate a pinion to spin the basket. The straight rack would be a simpler, more efficient means to rotate the pinion than the Bull curved rack member.

Bergen discloses a latching device where the rack and pinion operation provides a simplified arrangement for translating pivotal thumb lever movement into spindle rotational movement to turn a knob (col 9, ln 50-53). Lever (88) is pivotably mounted to frame (24), and has a narrow, elongated extension, (latch actuating end part (92)), which serves as the rod which is connected to rack plate (42) via the notch in the bottom of actuator plate (50). End part (92) linearly slides rack plate (42) in rack recess (28) of the frame. Rack plate includes rack (46), which meshes with pinion (52). Depressing the lever pivots the end part (rod), which slides the rack, rotating the pinion, and thus turning the knob (FIG. 1, 3, 5, 7, col 5, ln 28-36, 48-62, col 6, ln 41-64, col 7, ln 1-12, and col 8, ln 51-58).

It would have been obvious to one skilled in the art to modify the Bull/Wan handle and drive mechanism as per Bergen to add the

## INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.  
PCT/US08/81765

## Supplemental Box

end part extension (rod) from the handle lever as a means to slide the drive mechanism rack. Such design enables the user to employ a more effective force translation by the handle/rod pumping action in order to rotate the pinion and basket, while additionally providing a second, lowered handle position for improved storage of the device.

As per claim 16, Bull discloses the method of claim 15, but does not disclose wherein said driving assembly further comprises a rod connecting said handle to said driving mechanism, as per the combination of Wan and Bergen.

Wan discloses a salad spinner (10') that uses a drive mechanism (300) with a linearly actuating horizontal slider (310') and gear train (320') with leading gear (321') which acts as a straight rack. Rack meshes with second gear (322'), which acts as a pinion, so that gear train 320' serves to rotate the center ratchet assembly (400') to spin basket (200') (FIG. 17, 18B, 21, 23C, and para [0105, 0108, 0112]).

It would have been obvious to one skilled in the art to modify the Bull handle and drive mechanism as per Wan, such that the handle would linearly slide a straight rack which would act to rotate a pinion to spin the basket. The straight rack would be a simpler, more efficient means to rotate the pinion than the Bull curved rack member.

Bergen discloses a latching device where the rack and pinion operation provides a simplified arrangement for translating pivotal thumb lever movement into spindle rotational movement to turn a knob (col 9, ln 50-53). Lever (88) is pivotably mounted to frame (24), and has a narrow, elongated extension, (latch actuating end part (92)), which serves as the rod which is connected to rack plate (42) via the notch in the bottom of actuator plate (50). End part (92) linearly slides rack plate (42) in rack recess (28) of the frame. Rack plate includes rack (46), which meshes with pinion (52). Depressing the lever pivots the end part (rod), which slides the rack, rotating the pinion, and thus turning the knob (FIG. 1, 3, 5, 7, col 5, ln 28-36, 48-62, col 6, ln 41-64, col 7, ln 1-12, and col 8, ln 51-58).

It would have been obvious to one skilled in the art to modify the Bull/Wan handle and drive mechanism as per Bergen to add the end part extension (rod) from the handle lever as a means to slide the drive mechanism rack. Such design enables the user to employ a more effective force translation by the handle/rod pumping action in order to rotate the pinion and basket, while additionally providing a second, lowered handle position for improved storage of the device.

As per claim 18, Bull discloses the method of claim 17, but does not disclose wherein the step of actuating comprises pivotally rotating said handle about a second axis in the direction of the cover assembly and moving said rack which rotates said pinion.

Wan discloses a salad spinner (10') that uses a drive mechanism (300) with a linearly actuating horizontal slider (310') and gear train (320') with leading gear (321') which acts as a straight rack. Rack meshes with second gear (322'), which acts as a pinion, so that gear train 320' serves to rotate the center ratchet assembly (400') to spin basket (200') (FIG. 17, 18B, 21, 23C, and para [0105, 0108, 0112]).

It would have been obvious to one skilled in the art to modify the Bull handle and drive mechanism as per Wan, such that the handle would linearly slide a straight rack which would act to rotate a pinion to spin the basket. The straight rack would be a simpler, more efficient means to rotate the pinion than the Bull curved rack member.

Bergen discloses a latching device where the rack and pinion operation provides a simplified arrangement for translating pivotal thumb lever movement into spindle rotational movement to turn a knob (col 9, ln 50-53). Lever (88) is pivotably mounted to frame (24), and has a narrow, elongated extension, (latch actuating end part (92)), which serves as the rod which is connected to rack plate (42) via the notch in the bottom of actuator plate (50). End part (92) linearly slides rack plate (42) in rack recess (28) of the frame. Rack plate includes rack (46), which meshes with pinion (52). Depressing the lever pivots the end part (rod), which slides the rack, rotating the pinion, and thus turning the knob (FIG. 1, 3, 5, 7, col 5, ln 28-36, 48-62, col 6, ln 41-64, col 7, ln 1-12, and col 8, ln 51-58).

It would have been obvious to one skilled in the art to modify the Bull/Wan handle and drive mechanism as per Bergen to add the end part extension (rod) from the handle lever as a means to slide the drive mechanism rack. Such design enables the user to employ a more effective force translation by the handle/rod pumping action in order to rotate the pinion and basket, while additionally providing a second, lowered handle position for improved storage of the device. Thus, this combination device would include, as per Bergen, a lever handle which would pivot about a non-central second axis. The handle would pivotally rotate down in the direction of the cover assembly, and move the sliding rack, which then rotates the pinion, and so, improving the spinning operation of the basket.

Claims 1-18 have industrial applicability as defined under PCT Article 33(4) because the subject matter can be made or used in industry.  
----- NEW CITATIONS -----